DEENDAYAL PORT AUTHORITY

Fax No.(02836)233172/239055 Website: www.deendayalport.gov.in Email: xentdkpt@gmail.com



ADMINISTRATIVE OFFICE POST BOX NO. 50 GANDHIDHAM (Kutch) PIN 370 201

*************	*************
No: TD/WK/7850/	Date: 22/02/2023
To,	

Expression of Interest

Sub: - Renovation of Room No. 2 & 3 of Port Guest House, Gopalpuri.

Sir,

Deendayal Port Authority intends to carry out the subject work of ${\ \ }^{\ }$ D Division of Civil Engineering Department for a period of 30 days.

Kindly submit your Expression of Interest along with budgetary – offer for the items considered in preparation of the estimate under **Annexure-I**.

The rates quoted must be inclusive of all taxes, duties for performing scope of work & exclusive of GST. The GST applicable shall be shown separately, which shall not be considered for evaluation purposes.

Your expression of interest along with budgetary quotation for the above work should reach to the following address on or before 28/02/2023 by 15:00 Hrs.

Address: -

Office of the Executive Engineer (TD), TD Division, Administrative Office Building, Ground floor, Room No.128, Annexe, P.O. Box No. 50, Gandhidham – Kachchh.

Thanking you,

Yours faithfully,

Executive Engineer (TD)
Deendayal Port Authority

BUDGETARY OFFER

Sr				
	no.	Description	Unit	Rates
	1.	Providing & Applying Gypsum Punning up to thickness of 4 mm thick on existing walls to proper level & plumb including Groove Complete as		(In Rs.)
	2.	Panelling 3' Ht.: Providing and fixing 3 mm thk approved Veneer for wall panelling having matching superior grade. and with joints and grooves finished in melamine polish including 6 mm thk. Plywood backing on 37 mm x 25 mm Teak wood frame at 450 mm c/c and Teakwood mouldings of size 38 x 45 mm. Installation and provision of wooden pattern flooring with accepted quality standard with finish as per the acceptance standards set by the engineer in charge.	SFT	
	3.	Providing and installing Under counter Wash basin of size 18 inches with necessary corner filling by chemicals to avoid water leakage and including the Granite stand and wooden box of size 1ft*1ft in the bottom, the granite should be free from any damages and colour variation.	No.	
		Providing and laying SELECTED TILE size 600x1200 mm approximately 8 to 9 mm thick. approved Vitrified tile flooring of following size laid in combination of different shade on a avg. 40 mm thick bed of 1:4 cement mortar in proper line and level including neat cement float, filling joints with neat cement slurry, of appropriate colour curing and cleaning complete. Tiles shall be free of any variation in colour or texture. and applying pop protective cover on flooring and removing when directed. Vitrified tile fitting 1200 mm* 600 mm - Bathroom	SFT	
5	i. su of	Provide texture on the wall as per the proposed design with acceptance quality level set by engineer long with painting of wall and ceiling with minimum of 3 coats of approved paint of pproved shade & make including all necessary urfaces preparation. The ceiling and slab shall be eaned, filled with putty & applied with one coat primer so as to achieve an even surface to apply lint. As per the directions & to the satisfaction of the gineer.	SFT	

End