







[illegible]

The diagram shows a cross-section of a pile cap. The total width is 1.20 M. The reinforcement consists of 4 bars (4E) at the top and 4 bars (4E) at the bottom. The top bars are spaced at 0.30 M, and the bottom bars are spaced at 0.15 M. The total height of the cap is 0.40 M. The cap is supported by two piles, each with a diameter of 0.45 M. The distance between the centerlines of the piles is 2.00 M. The cap is 0.80 M high above the ground level (GL).

Figure 10.10 shows the elevation view of a wall and column. The wall is 3.10m high and 0.40m thick. The column is 0.40m wide and 0.15m high. The wall is supported by a foundation. The column is supported by a foundation. The wall is made of RCC M20 0.50m thick. The column is made of RCC 0.25 0.15m thick. The wall is on a SAND 0.15m thick. The column is on a SAND 0.15m thick. The wall is on a CL. The column is on a CL.

DEEN DAYAL PORT AUTHORITY		DRG NO :-
DEVELOPMENT OF AREA ADJACENT TO TUNA - GIM TRUCK BY EARTHORK IN EMBANKMENT FROM 4.00 KM. TO TAKE OFF-POINT FOR DOUBLING OF LINE TO FACILITATE UPCOMING NEW PROJECTS AT TERRA		DATE
 DRG BY	 CH. SRI	 A. N. S. R.

DEEN DAYAL PORT AUTHORITY		DRG NO :-
DEVELOPMENT OF AREA ADJACENT TO TUNA - GIM TRUCK BY EARTHORK IN EMBANKMENT FROM 4.00 KM. TO TAKE OFF-POINT FOR DOUBLING OF LINE TO FACILITATE UPCOMING NEW PROJECTS AT TERRA		DATE
 DRG BY	 CH. SRI	 A. N. S. R.