


दीनदयाल पत्तन प्राधिकरण  
DEENDAYAL PORT AUTHORITY

An ISO 9001:2000 Certified Port

(Ministry of Ports, Shipping & Waterways, Govt. of India)

दूरभाष / Tel : 02836 223912  
फैक्स / Fax : 02836 220050  
इ. मेल : tddivisionkpt@gmail.com



अभिशासी अभियंता का कार्यालय (टी.डी)  
Office of the Executive Engineer (TD)  
उपभवन / Annexe Building  
ए ओ बिल्डिंग पोस्ट बॉक्स न. 50  
A.O. Building, Post Box No 50  
गांधीधाम (कच्छ) / Gandhidham (Kutch)

No.TW/WK/7913-I/EOI/ 2355

Date :13/03/2026

To,

-----,  
-----,  
-----,

**EXPRESSION OF INTEREST**

Sub: Construction of Conference Hall at A.O.Building, Gandhidham

Sir,

Kindly submit your Expression of Interest (EOI) along with budgetary quotation offer for the subject work for the items considered for preparation of the Estimate under (Annexure-I)

The rates quoted must be inclusive of all taxes, duties for performing scope of work & Exclusive of GST. Applicable GST shall be shown separately, which shall not be considered for evaluation purpose.

Your Expression of Interest submit along with budgetary quotation for the above work should be reach to following address by Registered Post/Speed Post/ Courier on or before **23.03.2026 by 16:00 Hrs.**

Thanking you,

To,  
Office of Executive Engineer (TD),  
Room No. 103, A.O. Building Annexe  
Deendayal Port Authority,  
Gandhidham-Kutch-370201

Yours faithfully,

Executive Engineer (TD)  
Deendayal Port Authority

## Annexure-I

Sr. No	Description	Unit	Rate
1	<p>Wooden Flooring : Wooden Flooring, Beading &amp; Skirting : Providing and Fixing premium Commercial laminated Wooden flooring of selected by architect fixing in proper shape and true line level, including fixing with primary base 3-4 mm thick including 0.9 micron polythene to protect the seepage . Wooden Flooring planks of size 1214mm x 141.50mm x 10mm thick fixing on exacting floor. Remove &amp; preliminary clear all dirt and dust, necessary apply adhesive tools etc. complete as per guideline of Architect/Consultant. Rates are incl. the Beading and Skirting Beading:</p> <p>The sub-grade shall be cleaned, wetted and mopped. The bedding shall then be laid evenly over the surface tamped and corrected to desired level and allowed to harden enough to offer a rigid cushion to tiles and to enable the mason to place wooden planks across and squat on it. The laminated wooden tiles shall be laid on 8mm. th. Base if found un level flooring leveled it by white cement or cement mortar bedding of 12 mm. thick in C.M. 1 : 3. The mortar shall have sufficient plasticity for laying and there shall be no hard lumps that would interfere with the evenness of bedding. The base shall be cleared and well wetted. 75mm X 20mm thick skirting : Providing and fixing wooden 75mm X 20mm thick skirting of including one side molding finish same as per flooring patterns etc. Rates are including laying and removing of floor protection sheet etc. complete.(work for all the floors &amp; Levels)</p>	M2	
2	<p>Providing and fixing automated motorized Arabian curtain of fabric of size 0.5mm to 2mm thick featuring convenience and smart designs as per directed by Engineer in-charge.</p>	M2	
3	<p>Providing and fixing of panel board for electric fixture with 0.23m height including 18mm plywood side top &amp; bottom &amp; 12mm plywood on front &amp; 6mm plywood on backside on front plywood with 1mm bottom laminated</p>	M2	

	sheet on top & sides, all the material should be used for approved quality brand & shed complete with cost of nails, fevicol, screws, taxes etc., of all labour & materials as directed by Engineer-in-charge.		
4	Providing and fixing 12 mm thick frosted glass partition between working tables (As Shown In Drawing) including cost of "D" shape brackets, screws, making the edges of glass beveled on all sides, taxes complete with all labour and material.	M2	
5	Providing & fixing of executive 360' revolving chair with Medium back and ss body base with wheels & pneumatic up & down with one point locking mechanism.	Nos	
6	Providing & fixing of executive 360' revolving chair with low back visitor chair and ss body base with wheels & pneumatic up & down with one point locking mechanism.	Nos	
7	Providing and Fixing of 12mm thick frosted Glass railing fixing in 37mm thick S.S. 304 box pipe on top and bottom and 4 meter CLC vertical pipe fixed with S.S. bracket ib terrace including all material and Labour as directed by Engineer-in-charge.	RMT	
8	Providing and fixing metal ceiling system (.4 to .7 mm thick)consisting of factory-finished metal panels/tiles made of powder-coated galvanized steel or aluminum, of approved size, design, and perforation where required, with a suspended grid framework made from galvanized steel sections. The system shall be suspended from the structural ceiling using GI hangers, rods, and fasteners, including necessary clips, carriers, and accessories to complete the installation.	M2	
9	Brick Cladding (Size 230 mm x 75mmx20mm)	M2	
10	Chemical Adhesive	KG	
11	Apoxy grout filler	KG	
12	Water Proofing Compound	Lit	
13	Velvet touch paint	Lit.	
14	Primer	Kg	
15	19mm thick Plywood	M2	
16	1.0mm thick laminated sheet	M2	
17	Lock	Nos	
18	Handle	Each	
19	Plywood 18mm thick	M2	