



## Tender Details

Tender Details > **Tender Consolidated Details**

Tender ID: 300968	IFB/Tender Notice No.:HD-10/26	Description of Material/Name of Work: Construction of Toilet Blocks and Rest Shelters at Berth no. 1 to 10 and at Back up area of Cargo jetty area at New Kandla
ECV (INR):59237218.00	Last Date For Bid Submission: 10-06-2026 16:00	Tender Type/Tender Category :Open/WORKS
Location: Kachchh	Department: Deendayal Port Authority	Sub Department: Town Development Division

### View Tender Items

[Civil Work Boq](#) || [Civil Work Boq Item 46 Onwards](#) || [Electrical Part BOQ](#) || [View All Subwork](#)

#### Civil work boq

Item No.	Item Description	Qty	Unit
1	Earth work in excavation in all kind of soil / Ashphaled surface / Cemented surface by mechanical means (Hydraulic excavator)/manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and lift upto 1.5 m, as directed by Engineer-in-charge.	2924.290	m3
2	Extra for every additional lift of 1.5 m or part thereof in excavation / banking excavated or stacked materials.	450.050	m3
3	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.	843.590	m3
4	Filling in Foundation with Black Trap stone Boulder including supply of Boulder and preparing surface complete.	450.050	m3
5	Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete.	1312.020	m3

Item No.	Item Description	Qty	Unit
6	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:3:6 (1 Cement : 3 coarse sand : 6 graded stone aggregate 40 mm nominal size).	262.020	m3
7	Providing and laying in position machine batched and machine mixed design mix M-30 grade cement concrete for reinforced cement concrete work, using cement content as per approved design mix, including pumping / placing of concrete to site of laying including the cost of centering, shuttering, finishing but excluding the cost of reinforcement, including admixtures in recommended proportions as per IS: 9103 to accelerate, retard setting of concrete, improve workability without impairing strength and durability as per direction of Engineer-in-charge. (A) For work upto plinth level	1389.170	m3
B	work above Plinth level UPTO FLOOR FIVE LEVEL SILL	356.520	m3
8	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete . Thermo-Mechanically Treated bars of grade Fe- 500D or more. (I) Below Plinth Level	213886.300	KG
II	Above Plinth level	52178.000	KG
9	Reclamation of area for plot & approach road with mechanical plants equipments with quarry spall not exceeding 125 mm th. Including cost of excavation royalty taxes loading, unloading, transportation, spreading to required level, levelling, dressing in a layer of not more than 300 mm etc. & wet consolidation by loaded trucks movement and at top with powe vibratory roller etc. complete with all labour and material as directed by Engineer-in-charge.	3762.770	m3
10	Random rubble masonry with hard stone in foundation and plinth including levelling up with cement concrete 1:6:12 (1 cement : 6 coarse sand : 12 graded stone aggregate 20 mm nominal size)	355.280	m3
11	Brick work with common burnt clay machine moulded perforated bricks of class designation 12.5 conforming to IS: 2222 in superstructure above plinth level up to floor five level in cement mortar 1:4 (1 cement : 4 coarse sand) : (A) In superstructure above plinth level up to floor V level in all shapes and sizes in :	520.260	m3

Item No.	Item Description	Qty	Unit
12	Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia & length ( hold fast lugs or dash fastener shall be paid for separately). Second class teak wood	2.780	m3
13	Providing and fixing ISI marked flush door shutters conforming to IS :2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood and well matched teak and laminate with sunmica sheet 1mm thick on both faces of shutters. 35 mm thick	48.900	m2
14	Providing and fixing bright finished brass butt hinges with necessary screws etc. complete : 125x85x5.5 mm (heavy type)	159.000	each
15	Supplying & fixing the following fixtures of brass of approved quality to the doors, windows, ventilators etc. complete as directed by Engineer-in-Charge.	26.000	each
16	Providing and fixing bright finished brass tower bolts (barrel type) with necessary screws etc. complete :Brass tower bolt (barrel type) 250x10 mm	26.000	each
17	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868 ) transparent or dyed to required colour or shade, with necessary screws etc. complete : 250x10 mm	27.000	each
18	Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :	54.000	each
19	Providing and fixing bright finished brass handles with screws etc.complete: 125 mm	52.000	each
20	Providing and fixing bright finished Brass door latch 250x16x5 mm (0.350 kg)	80.000	each

Item No.	Item Description	Qty	Unit
21	<p>Providing and fixing factory made uPVC white colour sliding glazed window upto 1.50 m in height dimension comprising of uPVC multi- chambered frame with in-built roller track and sash extruded profiles duly reinforced with 1.60 ± 0.2 mm thick galvanized mild steel section made from roll forming process of required length (shape &amp; size according to uPVC profile),appropriate dimension of uPVC extruded glazing beads and uPVC extruded interlocks, EPDM gasket, wool pile, zinc alloy (white powder coated) touch locks with hook, zinc alloy body with single nylon rollers (weight bearing capacity to be 40 kg),G.I fasteners 100 x 8 mm size for fixing frame to finished wall and necessary stainless steel screws etc. Profile of frame &amp; sash shall be mitred cut and fusion welded at all corners, including drilling of holes for fixing hardware's and drainage of water etc.After fixing frame the gap between frame and adjacent finished wall shall be filled with weather proof silicon sealent over backer rod of required size and of approved quality, all complete as per approved drawing &amp; direction of Engineer-in-Charge. (Single / double glass panes, wire mesh and silicon sealant shall be paid separately) Two track two panels sliding window made of (small series) frame 52 x 44 mm &amp; sash 32 x 60 mm both having wall thickness of 1.9 ± 0.2 mm and single glazing bead of appropriate dimension. (Area of window upto 1.75 sqm)</p>	99.000	m2
22	<p>Providing and fixing factory made uPVC door frame made of uPVC extruded sections having an overall dimension as below (tolerance ±1mm), with wall thickness 2.0 mm (± 0.2 mm), corners of the door frame to be Jointed with galvanized brackets and stainless steel screws,joints mitred and Plastic welded. The hinge side vertical of the frames reinforced by galvanized M.S. tube of size 19 X 19 mm and 1mm (± 0.1 mm) wall thickness and 3 nos. stainless steel hinges fixed to the frame complete as per manufacturer's specification and direction of Engineer-in-charge Extruded section profile size 48x40 mm</p>	45.900	mtr

Item No.	Item Description	Qty	Unit
23	<p>Providing and fixing to existing door frames. 24 mm thick factory made PVC door shutters made of styles and rails of a uPVC hollow section of size 59x24 mm and wall thickness 2 mm (<math>\pm 0.2</math> mm) with inbuilt edging on both sides. The styles and rails mitred and joint at the corners by means of M.S. galvanised/ plastic brackets of size 75x220 mm having wall thickness 1.0 mm and stainless steel screws. The styles of the shutter reinforced by inserting galvanised M.S. tube of size 20x20 mm and 1 mm (<math>\pm 0.1</math> mm) wall thickness. The lock rail made up of 'H' section, a uPVC hollow section of size 100x24 mm and 2 mm (<math>\pm 0.2</math> mm) wall thickness, fixed to the shutter styles by means of plastic/galvanised M.S. 'U' cleats. The shutter frame filled with a uPVC multi-chambered single panel of size not less than 620 mm, having over all thickness of 20 mm and 1 mm (<math>\pm 0.1</math> mm) wall thickness. The panels filled vertically and tie bar at two places by inserting horizontally 6 mm galvanised M.S. rod and fastened with nuts and washers, complete as per manufacturer's specification and direction of Engineer-in-charge. (For W.C. and bathroom door shutter).</p>	50.060	m2

Item No.	Item Description	Qty	Unit
24	<p>Providing and fixing factory made uPVC white colour casement/casement cum fixed glazed windows comprising of uPVC multi-chambered frame, sash and mullion (where ever required)extruded profiles duly reinforced with <math>1.60 \pm 0.2</math> mm thick galvanized mild steel section made from roll forming process of required length (shape &amp; size according to uPVC profile), uPVC extruded glazing beads of appropriate dimension, EPDM gasket, stainless steel (SS 304 grade) friction hinges, zinc alloy (white powder coated) casement handles, G.I fasteners 100 x 8 mm size for fixing frame to finished wall, plastic packers, plastic caps and necessary stainless steel screws etc. Profile of frame &amp; sash shall be mitred cut and fusion welded at all corners, mullion (if required) shall be also fusion welded including drilling of holes for fixing hardware's and drainage of water etc. After fixing frame the gap between frame and adjacent finished wall shall be filled with weather proof silicon sealant over backer rod of required size and of approved quality, all complete as per approved drawing &amp; direction of Engineer-in-Charge. (Single / double glass panes and silicon sealant shall be paid separately) Note: For uPVC frame, sash and mullion extruded profiles minus 5 percent tolerance in dimension i.e. in depth &amp; width of profile shall be acceptable. Casement window single panel with S.S. friction hinges (300 x 19 x 1.9 mm), made of (small series) frame 47 x 50 mm &amp; sash 47 x 68 mm both having wall thickness of <math>1.9 \pm 0.2</math> mm and single glass pane glazing bead of appropriate dimension. (Area of window upto 0.75 sqm.)</p>	9.720	m2
25	<p>Structural steel work in single section, fixed with or without connecting plate, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.</p>	3825.000	kg
26	<p>Plastering with cement mortar 1 : 4 including racking out joints, scrubbing &amp; cleaning, finishing smooth curing including racking out joints etc. complete for interior / exterior plastering upto floor five level. 12 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand)</p>	8935.390	m2

Item No.	Item Description	Qty	Unit
27	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. Granite of any colour and shade Area of slab over 0.50 sqm	818.270	m2
28	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08 percent and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Size of Tile 600x600 mm Grouting the joints of flooring tiles having joints of 3 mm width, using epoxy grout mix of 0.70 kg of organic coated filler of desired shade (0.10 kg of hardener and 0.20 kg of resin per kg), including filling /grouting and finishing complete as per direction of Engineer-in-charge.	857.270	M2
29	Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab, including rubbing and polishing complete with base of cement mortar 1 : 4 (1 cement : 4 coarse sand) : (a) 25 mm thick	189.000	M2
30	Providing and laying Vitrified tiles in different sizes (thickness to be specified by the manufacturer), with water absorption less than 0.08 percent and conforming to IS: 15622, of approved brand & manufacturer, in all colours and shade, in skirting, riser of steps, laid with cement based high polymer modified quick set tile adhesive (water based) conforming to IS: 15477, in average 9 mm thickness, including Grouting the joints of flooring tiles having joints of 3 mm width, using epoxy grout mix of 0.70 kg of organic coated filler of desired shade (0.10 kg of hardener and 0.20 kg of resin per kg), including filling /grouting and finishing complete as per direction of Engineer-in-charge. (a) Size of Tile 600 x 600 mm	4295.240	m2

Item No.	Item Description	Qty	Unit
31	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey,Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement :4 Coarse sand), jointing with grey cement slurry @ 3.3kg/sqm including pointing the joints with white cement and matching pigment etc., complete.	132.240	M2
32	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in- Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	196.000	M2
33	Providing and laying the water proofing on terrace by providing avrage 90 mm thick of brick bat coba to necessary gradient and joint filled in CM 1:3 with mixing water proofing compound as per manufacturer' specification , rough to receive china mosaic (broken piece of china mosaic) of approved colour and pattern over top surface in CM 1:3 and with cement slurry, giving proper slope to drain out rain water, compaction, curing etc., complete all labour and materials as directed by Engineer-in-charge.	981.830	m2
34	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required :	15.000	each
35	Providing and fixing wash basin with C.I. brackets, 15 mm dia CP Brass single hole basin mixer of approved quality and make, including painting of fittings and brackets, cutting and making good the walls wherever required:- (a) White Vitreous China Wash basin size 550x400 mm with a 15 mm CP Brass single hole basin mixer	9.000	each
36	Providing and fixing brass bib cock of approved quality : 15 mm nominal bore	87.000	each

Item No.	Item Description	Qty	Unit
37	Providing and fixing brass stop cock of approved quality : 15 mm nominal bore	72.000	each
38	Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively.	15.000	each
39	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge.(Concealed work, including cutting chases and making good the walls etc) (a) 15 mm nominal outer dia Pipes	216.000	mtr
b	20 mm nominal outer dia Pipes	130.000	mtr
c	25 mm nominal outer dia Pipes	100.000	mtr
40	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings This includes jointing of pipes & fittings with one step CPVC solvent cement, trenching, refilling & testing of joints complete as per direction of Engineer in Charge. 32 mm nominal outtr dia pipes external work	100.000	mtr
41	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion,(i) Single socketed pipes. Pipe 75 mm outer dia.	200.000	Mtr
b	110 mm dia.	200.000	Mtr
42	Providing and placing on terrace (at all floor levels) polyethylene water storage tank, IS : 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank.	26000.000	ltr
43	Applying priming coats with primer of approved brand and manufacture, having low VOC (Volatile Organic Compound ) content. With water thinnable cement primer on wall surface having VOC content less than 50 grams/litre	2995.680	M2
44	Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.	1651.680	m2

Item No.	Item Description	Qty	Unit
45	Wall painting with acrylic emulsion paint of approved brand and manufacture to give an even shade : Two or more coats on new work	1651.680	m2

#### Civil work boq item 46 onwards

Item No.	Item Description	Qty	Unit
46	Providing and fixing PTMT 15 mm Urinal spreader size 95x69x100 mm with 1/2" BSP thread and shapes, weighing not less than 60 gms.	15.000	Each
47	Supplying, testing, commissioning RO Plants of 150 Litre per hour capacity (including PVC water tank of 500ltr capacity) of approved make which consists of all necessary parts viz motor pump of required capacity, multipart valve, 20" bowl & filter silver process of high pressure pump of required capacity, multipart valve, 20" bowl & filter silver process of high pressure pump of required capacity, membrane, Rotameter, pressure meter, electric panel with M.S. Cabinet all necessary Electric & other connection required to commissioned the RO Plant which gives the required TDS complete with loading, unloading & Transportation, Installation including all taxes with one year warrantee and maintenance free.	7.000	Each
48	Painting Steel work with Deluxe Multi Surface Paint to give an even shade. Two or more coat applied @ 0.90 ltr/ 10 sqm over (an under coat of existing primer) of approved brand and manufacture	158.400	M2
49	Painting wood work with Deluxe Multi Surface Paint of required shade. Two or more coat applied @ 0.90 ltr/10 sqm over an under coat of primer applied @0.75 ltr/10 sqm of approved brand and manufacture	51.070	m2
50	Providing and laying 60mm thick factory made cement concrete interlocking paver block of M -30 grade made by block making machine with strong vibratory compaction, of approved size, design & shape, laid in required colour and pattern over existing concrete surface. all complete as per the direction of Engineer-in-charge.	9408.710	m2
51	Collection, and filling Black stone dust / Grit in foundation and trenches in a layer of avg 20 cm including cost of Excavation ,Royalty, loading, unloading and transportation at the site of work.	2770.576	m3
52	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	971.400	m2

Item No.	Item Description	Qty	Unit
53	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture	672.000	m2

### Electrical part BOQ

Item No.	Item Description	Qty	Unit
1	Supply, Installation, Testing and commissioning of Feeder Panel for distribution of underground power supply as per technical specification No.1 (a) Feeder panel as per technical (i)Supply	10.000	No.
(ii)	Installation, Testing and commissioning	10.000	No.
2	Supply at site 4 Core, LT armoured aluminium conductor XLPE cable of 1.1kV grade of following type & size as per Technical Specification No. 2. (a) 4 Core X 95 Sq.mm	2100.000	Mtr.
(e)	4 Core X 16 Sq.mm	400.000	Mtr.
(f)	4 Core X 4 Sq.mm	500.000	Mtr.
3	Laying of LT armoured aluminium conductor XLPE cable of 1.1kV grade of type 4 core, of size 4 sqmm to 95 Sq.mm through following type as per Technical Specification No. 3. (a) Hard/Soft Soil	1550.000	Mtr.
(b)	Road/RCC Crossing	650.000	Mtr.
(c)	On wall through saddles & clamps	450.000	Mtr.
(d)	In GI Class-B Pipe	350.000	Mtr.
4	Providing & fixing following concealed wiring for single phase sub-circuit from the main switch /meter. DBs / MCBs to the switch board as per Technical Specification No. 4. (a) with 2 x 2.5 sq.mm. copper conductor (single phase and neutral)	1950.000	Mtr.
(b)	with 2 x 4 sq.mm. copper conductor (single phase and neutral)	1000.000	Mtr.
5	Providing and Fixing concealed wiring for light/tube/bell point with PVC insulated single core standard 1.5 Sq.mm. copper conductor wire as per Technical Specification No. 5.	259.000	No.
6	Providing and Fixing concealed wiring for Fan point with PVC insulated single core standard 1.5 Sq.mm. copper conductor wire & single/twin module step cut electronic fan regulator as case may be as per Technical Specification No. 6.	74.000	No.
7	Providing and fixing concealed wiring for 5/6A X250 Volt. As per Technical Specification No. 7. (a) Full plug point.	88.000	No.
(b)	Half Plug Point.	54.000	No.

Item No.	Item Description	Qty	Unit
8	Providing and fixing concealed wiring, for 15/16A X250 Volt Power point as per Technical Specification No. 8.	23.000	No.
9	Supply & installation of following type distribution board along with complete with DP, SP MCB & ELCB as per Technical specification No. 9. (a) Supply	15.000	No.
(b)	Installation & Commissioning	15.000	No.
10	Supply & Fixing of 4ft, LED Tube white Light Fixture of 20-22 Watt with complete accessories as per Technical Specification No. 10. (a) Supply	137.000	No.
(b)	Fixing	137.000	No.
11	Supply & Fixing of 1200mm sweep ordinary ceiling fan with all accessories as per Technical Specification No. 11. (a) Supply	74.000	No.
(b)	Fixing	74.000	No.
12	Supply & Fixing of 225mm sweep Exhaust fan with all accessories as per Technical Specification No. 12. (a) Supply	43.000	No.
(b)	Fixing	43.000	No.
13	Supply & Fixing of 10Watt LED bulk Head light fixture with all accessories as per Technical Specification No. 13. (a)Supply	44.000	No.
(b)	Fixing	44.000	No.
14	Supply & Fixing of 60 Watt LED Street light fixture with all accessories as per Technical Specification No. 14. (a) Supply	94.000	No.
(b)	Fixing	94.000	No.
15	Supply of Hot presss moulded SMC junction box with outer Dia 140 x 140 x 95 mm with left hinged door as per Technical Specification No. 15. (a) Supply	94.000	No.
(b)	Fixing	94.000	No.
16	Providing & fixing M S finish Double Door MCB distribution board with following ways from incoming/outgoing with suitable common bus bar and neutral link arrangement as per TechnicalSpecification No. 16. (i) MCB DB - 8 ways (a) Supply	15.000	No.
(b)	Fixing	15.000	No.
(II)	MCB DB - 12 ways (a) Supply	10.000	No.
(b)	Fixing	10.000	No.
(III)	MCB DB - 16 ways (a) Supply	10.000	No.
(b)	Fixing	10.000	No.
17	Providing & fixing following type of MCBs of approved make in distribution board with all necessary wiring & connection as per Technical Specification No. 17. (I) 40A, 415/440V, 4P (TPN) MCB (a) Supply	30.000	No.
(b)	Fixing	30.000	No.

Item No.	Item Description	Qty	Unit
(II)	6 -32 A 230/250V DP MCB (a) Supply	15.000	No.
(b)	Fixing	15.000	No.
(III)	6 -32 A 230/250V SP MCB (a) Supply	100.000	No.
(b)	Fixing	100.000	No.
18	Preparation earthing station, chemical treated back filled compound earthing system with Pipe-In-Pipe 50 mm Dia GI type 2 Mtr Depth, Maintenance free. as per Technical Specification No. 18.	30.000	No.
19	Supply, Laying, connecting of GI Strips Connecting earth station to the equipment as per Technical Specification No. 19. 25x3mm thick (a) Supply	500.000	Mtr
(II)	Laying, connecting	500.000	Mtr.
20	Providing & connecting following type earth wire for earth station to Main DB / Meter/SB as per requirement as per Technical Specification No. 20. 8 (a) SWG GI earthing wire.	500.000	Mtr.

## Notes

Subwork Name	Description	Period of Completion	Scope of Subwork
Civil work boq	As per tender	18.0	As per tender
Civil work boq item 46 onwards	As per tender	18.0	As per tender
Electrical part BOQ	As per tender	18.0	As per tender

BACK